



RS-232 Pass-Through : Using Aux. Y cable with AC power adapter.  
 RS-485: Using 9A 9B 4B connectors (no Power adppter)  
 PC USB : AC power adapter required  
 USB Hub Host: 5V DCpower pass-though, support for USB1.1 and 2.0 for up to 16 devices (optional)  
 IBM Retail USB Sure POS compatible. (no power Adapter)  
 Ethernet10/100 BaseT : Optional Port. Cable not supplied.

**Memory:**

Flash : 4MB to 16MB  
 SDRAM: 16MB to 64 MB

*Dimension (reference)*

Width:7.3in (18.5cm )  
 Depth : 7.5in (19.2cm)  
 Height :2.in (5.1cm)  
 Weight: 2 lb.(.9kg)

**Verifier 300LC 2.0 (8 Qty)**

***Specification: (Cross Match Verifier 300LC 2.0 is an optical USP 2.0 finger print scanner )***

Device Name:	Verifier 300LC 2.0
Manufacturer	Cross Match Technologies inc
Device Connection	USB 2.0
Supported OS	Micro soft Windows
Sensor Resolution	500dbi
<b><i>Image picture area (Platen)</i></b>	
Sensor type	Optical
Device Size	62x162x83mm(2.4"x6.4"x3.3")
Device Weight	450 grams (1.0lbs)
Operation Temperature	-18°C ~ +40°C
Operating Humidity	10-90% ( non-condensing,splash-resistant)

